

Konstruktionsvollholz (KVH)

KVH Nsi, Fi./Ta., keilgezinkt

Qualität: Nsi (für den nicht sichtbaren Bereich) S 10 nach DIN 4074,
ca. 15 +/- 3% HF, Oberfläche: allseitig gehobelt & gefast

Dim. In.mm	2,00 m	3,00 m	5,00 m	6,50 m	7,0 0m	7,50 m	8,00 m	8,50 m	9,00m	10,50 m	13,00m
80x80			L								B
80x100			L				B				B
80x120	L	L	L	L			B				L
80x140	L	L	L	L			B				L
80x160	L	L	L	L	B	B	B	B	B	B	L
80x180			L	L	B	B	B	B	B	B	L
80x200			L	L	B	B	B	B	B	B	L
80x220				L	B	B	B	B	B	B	L
80x240			L	L	B	B	B	B	B	B	L
80x260											B
80x280											B
80x300 (Duo)										B	B
100x100	L	L	L	L			B				L
100x120			B	L							L
100x140			B								B
100x160				L			B			B	L
100x180							B			B	B
100x200				L			B			B	L
100x220				L			B			B	L
100x240				L			B			B	L
100x260											B
100x280											B
100x300 (Duo)											B

L: Lagerware **B: Bestellware**